

TECHNICAL STANDARDS & SAFETY AUTHORITYMBRE DE COMMERCE ET

14th Floor, Centre Tower

3300 Bloor Street West 0 1 6 Canada M8X 2K4

0 7, 06, 1 3



J.M. TOUIN

D'INDUSTRIE DE LYON

STATUTORY DECLARATION Registration of Fittings Jean-Pierre Richer, President (Name and Position, e.g. President, Plant Manager, Chief Engineer) of descote SAS (Name of Manufacturer) Located at _____9 avenue Jean Jaures 69320 Feyzin - France 0033472892525 0033472892500 (Telephone No.) (Fax No.) (Plant Address) do solemnly declare that the fittings listed hereunder, which are subject to the Technical Standards and Safety Act, Boilers and Pressure Vessels Regulation, comply with all of the requirements of ASME B16-34, B16-5, B16-10 and B31-3 (Title of recognized North American Standard) which specifies the dimensions, materials of construction, pressure/temperature ratings, identification marking the fittings and service; or are not covered by the provisions of a recognized North American standard and are therefore manufactured to comply with as supported by the attached data which identifies the dimensions, material of construction, pressure/temperature ratings and the basis for such ratings, the marking of the fitting for identification and service. I further declare that the manufacture of these fittings is controlled by a quality system meeting the requirements of ISO 9001 which has been verified by the following authority, Lloyd's Register type fittings. In support of The items covered by this declaration, for which I seek registration, are category this application, the following information and/or test data are attached as follows: Technical + sales documents for 1500 series, 2100 series, 2020 series, 2200/2300 series, 2500 series, 900 series (drawings, calculations, test reports, etc.) Declared before me at_ in the ____AD 20___ day of ___ Commissioner for Oaths: (Printed name) (Signature of Declarer) (Signature) FOR OFFICE USE ONLY To the best of my knowledge and belief, the application meets the requirements of the Technical Standards and Safety Act, Boilers and Pressure Vessels Regulation, and MMERC CSA Standard B51 and is accepted for registration in Category Technical CRN: Standards DE and Safety LYON Authority Registered by: Dated: NOTE: This registration expires on: Vu pour certification For scope. KK 2/7 matérielle de la Signature de M. R. CHER Pour le Président

Page 1/1



descote valves are in full compliance with design, dimensions, materials and service of ASME B16.34.

Series	Description	Pattern	Size	Pressure class	Temperature mini/maxi	Wall thickness	Materials
1500B (manual, actuated on-off, control)	Gland type globe valve	straight angle 3-way	3/8" to 12"	ANSI class 150 to 2500 lbs	-320°F to +1500°F	according to Asme B16.34	10
2100 series (manual, actuated on-off, control)	Bellows sealed globe valve	straight angle 3-way	3/8" to 16"	ANSI class 150 to 2500 lbs	-320°F to +1500°F	according to Asme B16.34	
2020 (manual, actuated on-off, control)	Instrumentation bellows sealed globe valve	straight angle	1/8" to 1/2"	ANSI class 600 to 2500 lbs	-320°F to +1500°F	according to Asme B16.34	
2200/2300	Double sealing device for storage tank	angle	1" to 8"	ANSI class 150 to 600 lbs	-150°F to +750°F	according to	10
2500 series (manual, actuated on-off, control)	Bellows sealed globe valve	straight angle 3-way	3/8" to 12"	ANSI class 150 to 2500 lbs	-320°F to +1500°F	Asme B16.34 according to Asme B16.34	Materials as per ASME B16.34
921 (manual)	Bellows sealed globe valve for railcar transportation	angle	- 1 ⁱⁱ	ANSI class 300 lbs	-40°F to +250°F	according to Asme B16.34	an and
922/926 (manual)	Bellows sealed globe valve for railcar transportation	angle	1"	ANSI class 300 lbs	-40°F to +250°F	according to Asme B16.34	nar II
925/926 (actuated)	Bellows sealed globe valve for railcar transportation	angle	1"	ANSI class 300 lbs	-40°F to +250°F	according to Asme B16.34	₩/ I

